



320 Northpoint Parkway SE  
 Suite B & C  
 Acworth, GA 30102 USA  
 Tel: 770-529-6800  
 Fax: 770-529-6840  
[www.dmswireless.com](http://www.dmswireless.com)

September 2008

<b>CPE FLAT PANEL ANTENNA</b>	
<b>Customer Premises Equipment</b>	
<b>2400 - 2830 MHZ CPE2412VH</b>	
<b>Electrical Data</b>	
Gain (dBi)	12
Beamwidth (degrees)	65H 58V
Front to Back Ratio (dB)	>15
VSWR (typical)	1.5 or less
Rated Wind Velocity	210 kmh/130mph
Maximum Power (watts)	100
Polarization	Vertical/Horizontal
Input Impedance	50 Ohms
<b>Physical Data</b>	
Construction	Air Dielectric
Radiation Element	Aluminum Alloy
Radome Material	UV Resistant ABS
Connector Interface	Female N
Structure	One Panel
Lightning Protection	Direct Ground
Fits Mast Size1 - 2"/28 -48mm	

Photos: Photos for CPE Series - CUSTOMER PREMISES EQUIPMENT - FLAT PLANAR ANTENNA

Photo may not be exact model.

Please note the construction, the materials and the mounting hardware are accurate in photos for all models, only size is different.

Specifications: Specifications subject to change without notice.

Any questions, please contact DMS WIRELESS

<http://www.dmswireless.com>  
[wireless@dmswireless.com](mailto:wireless@dmswireless.com)

All products FCA Warehouse, Acworth, GA 30102 USA

One year warranty: Repair or replacement, no freight included.

Contact DMS WIRELESS for RMA.

No returns accepted without RMA.