



320 Northpoint Parkway SE
 Suite B & C
 Acworth, GA 30102 USA
 Tel: 770-529-6800
 Fax: 770-529-6840
www.dmswireless.com

September 2008

CPE FLAT PANEL ANTENNA	
Customer Premises Equipment	
698 - 760 MHZ	
	CPE7008VH-75F
Electrical Data	
Gain (dBi)	8
Beamwidth (degrees)	88H 55V
Front to Back Ratio (dB)	>15
VSWR (typical)	1.5 or less
Rated Wind Velocity	210 kmh/130mph
Maximum Power (watts)	100
Polarization	Vertical/Horizontal
Input Impedance	75 Ohms
Physical Data	
Construction	Air Dielectric
Radiation Element	Aluminum Alloy
Radome Material	UV Resistant ABS
Connector Interface	Male F
Structure	One Panel
Lightning Protection	Direct Ground
Fits Mast Size	1 - 2"/28 -48mm

Photos: Photos for CPE Series - CUSTOMER PREMISES EQUIPMENT - FLAT PLANAR ANTENNA
 Photo may not be exact model.

Please note the construction, the materials and the mounting hardware
 are accurate in photos for all models, only size is different.

Specifications: Specifications subject to change without notice.
 Any questions, please contact DMS WIRELESS
<http://www.dmswireless.com>
wireless@dmswireless.com

All products FCA Warehouse, Acworth, GA 30102 USA
 One year warranty: Repair or replacement, no freight included.
 Contact DMS WIRELESS for RMA.
 No returns accepted without RMA.