



320 Northpoint Parkway SE
 Suite B & C
 Acworth, GA 30102 USA
 Tel: 770-529-6800
 Fax: 770-529-6840

GRID ANTENNAS

Wireless broadband grid antennas with passive feed for point to point, backhaul, or customer premises applications

RoHS Compliant

	WiMAX	WiMAX	WiMAX	WiMAX	WiMAX
2500 - 2686 MHZ	GA2515M/F	GA2519M/F	GA2521M/F	GA2524M/F	GA2539M/F

Electrical Data

Gain (dBi)	15	19	21	24	26.5
Front-Back Ratio (dBc)	<19	<22	<23	<24	<33
Return Loss (dB)	10	10	10	10	10
VSWR (typical)	1.5 or less	1.5 or less	1.5 or less	1.5 or less	1.5 or less
Beamwidth	21H 19V	16H 11V	12	8	9.3
Windload (lbs)	8	16	22	40	pdf data
Maximum Power	200 Watts Direct	200 Watts Direct	200 Watts Direct	200 Watts Direct	200 Watts Direct
Lightning Protection	Ground	Ground	Ground	Ground	Ground
Input Impedance	50 Ohms	50 Ohms	50 Ohms	50 Ohms	50 Ohms
Connector Interface	N Type	N Type	N Type	N Type	N Type
Polarization	Vert or Hor	Vert or Hor	Vert or Hor	Vert or Hor	Vert or Hor

Construction

Grid Reflectors	Zinc plated cold rolled steel with polyester powder coat				
Passive Feeds	Ultrasonic weld on UV stabilized ABS Plastic				
Connector/Cable	High grade microwave cable with male or female N connector, 24"				
Install Hardware	Polyester powder coat steel brackets with stainless steel hardware				
Fits Mast Size	1 - 2.5" 28-64mm	1 - 2.5" 28-64mm	1 - 2.5" 28-64mm	1 - 2.5" 28-64mm	1 - 2.5" 28-64mm