



320 Northpoint Parkway SE
 Suite B & C
 Acworth, GA 30102 USA
 Tel: 770-529-6800
 Fax: 770-529-6840
www.dmswireless.com

February 2010

GRID ANTENNAS	Wireless broadband grid antennas with arm to mount				
	Motorola Canopy Radios				
3650 - 3750 MHz					
	GAMC14R	GAMC18R	GAMC24R	GAMC32R	GAMC39R
Electrical Data					
Gain (dBi)	18	20.5	24.5	27	30
Return Loss (dB)	12	12	12	12	12
VSWR (typical)	1.5 or less	1.5 or less	1.5 or less	1.5 or less	1.5 or less
Beamwidth	8.5H 17V	8H 11V	13.7H 15V	9H 8V	9.3
Windload (lbs)	pdf data	pdf data	pdf data	pdf data	pdf data
Polarization	Vertical	Vertical	Vertical	Vertical	Vertical
	200 Watts	200 Watts	200 Watts	200 Watts	200 Watts
Lightning Protection	Direct Ground	Direct Ground	Direct Ground	Direct Ground	Direct Ground
Input Impedance	50 Ohms	50 Ohms	50 Ohms	50 Ohms	50 Ohms
Connector Interface	N Type	N Type	N Type	N Type	N Type
Construction					
Grid Reflectors	Zinc plated cold rolled steel with polyester powder coat				
Arm/Assembly	Polyester powder coat steel arm/assembly				
Connector/Cable	High grade microwave cable with male or female N connector				
Install Hardware	Polyester powder coat steel brackets with stainless steel hardware				
Fits Mast Size	1 - 2.5"	1 - 2.5"	1 - 2.5"	1 - 2.5"	1 - 2.5"
	28-64mm	28-64mm	28-64mm	28-64mm	28-64mm

Photos: Photos for GA Series - GRID REFLECTOR ANTENNA
 Photo may not be exact model.

Please note the construction, the materials and the mounting hardware are accurate in photos for all models, only size is different.

Specifications: Specifications subject to change without notice.

Any questions, please contact DMS WIRELESS

<http://www.dmswireless.com>
wireless@dmswireless.com

All products FCA Warehouse, Acworth, GA 30102 USA

One year warranty: Repair or replacement, no freight included.

Contact DMS WIRELESS for RMA.

No returns accepted without RMA.