



320 Northpoint Parkway SE
 Suite B & C
 Acworth, GA 30102 USA
 Tel: 770-529-6800
 Fax: 770-529-6840
www.dmswireless.com

February 2009

MAGNETIC MOUNT		
Mobile Omni Directional Antenna		
450 - 470 MHz	MA4503	MA4505
Electrical Data		
Gain (dBi)	3	5
Beamwidth (degrees)	360H 35V	360H 29V
VSWR (typical)	1.5 or less	1.5 or less
Rated Wind Velocity	210 kmh/130mph	210 kmh/130mph
Maximum Power (watts)	50	50
Polarization	Vertical	Vertical
Input Impedance	50 Ohms	50 Ohms
Lightning Protection	Direct Ground	Direct Ground
Physical Data		
Dipole Radiation Element	Magnesium Steel Alloy	Magnesium Steel Alloy
Mounting	Magnetic Base	Magnetic Base
Connector Interface	Male N	Male N
Structure	One Dipole	One Dipole
RG58-U Cable Length	12 Feet/3.65 Meters	12 Feet/3.65 Meters
Length - Dipole	16.75"/425 mm	31"/788 mm
Length - Base	4.25"/108 mm Round	4.25"/108 mm Round
www.dmswireless.com		

Photos: Photos for MA Series - MAGNETIC MOUNT ANTENNA
 Omni Directional

Photo may not be exact model.

Please note the construction, the materials and the mounting hardware
 are accurate in photos for all models, only size is different.

Specifications: Specifications subject to change without notice.

Any questions, please contact DMS WIRELESS

<http://www.dmswireless.com>

wireless@dmswireless.com

All products FCA Warehouse, Acworth, GA 30102 USA

One year warranty: Repair or replacement, no freight included.

Contact DMS WIRELESS for RMA.

No returns accepted without RMA.